



## **Hardcore Derby Promotions Youth Full-Size Fix it Plate Rules For 2025**

**Bash For cash youth full size-** All cars fresh or pre run are permitted 2 fix it plates. Fix it plates are permitted to be a max of 4"x4" x3/8" max square or parallelogram. If parallelogram, they must measure 4" tall and 4" wide at all points and must be exactly 7" between the two furthestmost points. Any more will be completely removed. No Nine wire outside of the permitted 2 strand on front bumper from core support and the two on rear bumper to within 6" of the bumper in taillight area. No frame shaping anywhere

**Washington Courthouse youth Team show-** All cars fresh of pre run may have 4 fix it plates. Fix it plates are permitted to be a max of 4"x4" x3/8" max square or parallelogram. If parallelogram, they must measure 4" tall and 4" wide at all points and must be exactly 7" between the two furthestmost points. Any more will be completely removed. You are permitted 4 locations of #9 wire to start in addition of the permitted 2 strand on front bumper from core support and the two on rear bumper to within 6" of the bumper in taillight area. Nine wire must not exceed 4 loops single strand per location or 2 loops of double braided.

Following the heat you will be allowed to add 6 locations of wire and 2 additional fix it plates.

No frame shaping anywhere

**Hardcore 2025 Tour youth Full size-** You may utilize a maximum of 6 fix it plates fresh or pre run. Fix it plates are permitted to be a max of 4"x 4" x3/8" max square or parallelogram. If parallelogram, they must measure 4" tall and 4" wide at all points and must be exactly 7" between the two furthestmost points. Any more will be completely removed. You are permitted 4 locations of #9 wire in addition of the permitted 2 strand on front bumper from core support and the two on rear bumper to within 6" of the bumper in taillight area. Nine wire must not exceed 4 loops single strand per location or 2 loops of double braided. **If at any point in the season you need to move a fix it plate to a different location, you must completely remove both the plate and the weld from the frame in its entirety. At no time will you be permitted to have more than 6 plates and 4 locations of wire. All re-stubs must be pre-approved by TJ McCullough 301-707-6870. \*\*\*\*Fresh or pre run you are permitted to form the outside wheel facing hump between the body mount in front of the rear wheel and immediately behind the rear wheel. No added metal and no welding.**

### **Youth nationals**

All cars may start with 2 fix it plates. Fix it plates are permitted to be 4"x4" x 3/8" max square or parallelogram. If parallelogram, they must measure 4" tall and 4" wide at all points and must be exactly 7" between the two furthestmost points. Any more will be completely removed. You are permitted 4 locations of #9 wire to start in addition of the permitted 2 strand on front bumper from core support and the two on rear bumper to within 6" of the bumper in taillight area. Nine wire must not exceed 4 loops single strand per location or 2 loops of double braided.

Following the heat you are permitted 4 additional 4"x 4" x 3/8" fix it plates and 6 additional locations of 9 wire.

**you are permitted to form the outside wheel facing hump between the body mount in front of the rear wheel and immediately behind the rear wheel. No added metal and no welding.**

**Any Questions Contact Tj McCullough at 301-707-6870**