

North of 80 Rules

CAGE

4 bar cage must stay in the driver's compartment

(From firewall to rear axle)

Cage material 6-inch max

Up to 4 vertical down legs to frame

32-inch-wide gas tank protector

2 — 3"x3" kickers from dash bar to back of factory location of A-arm if do not have distributor protector

No rear kickers

FRAME/BUMPERS

22'inch front bumper height to bottom

12" inch rear bumper to bottom

(enforced)

No plating frame other than what is specified

Frames may not be plated or reinforced internally

Front bumper plate may extend to the front edge of a- arm one side only

4"wide 3/8" thick

8" angle bracket for crossmember mounting

32" x3/8" hump plate

Rear bumper bracket 14"x3/8"

Frame seams may be welded. 10- 4"x6"x3/8" repair plates max

BODY

Doors may be plated and welded shut 1/4" material (1 layer only)

Trunk lid seams can be welded solid with 4"x1/4' strapping

Body patching is ok but not full sheeted cars

STEERING/Suspension

Aftermarket steering is
allowed

Front and rear suspension
may be locked

Leaf conversion is
permitted

***bump stops must be
installed to prevent rear
bumper height going
below 12

Any Questions Please Contact

Tyler

Finefrock 814-227-9322 or

Chris Firster 724-877-9999